

SPECIFICATIONS

FR0943986

Page 1 of 1

ITEM NO.	DESCRIPTION	CHECK IF AS SPECIFIED	DESCRIBE FULLY IF NOT AS SPECIFIED
1.	Trutest 800, Conventional and Intelligent System Detector Test Equipment with Telescopic pole to be used on a Simplex system		
	MAXIMUM working height 20 ft.		
	Average test time: 120 seconds		
	Average cleaning time: 120 seconds		
	Average calibration time: 40 seconds		
	Maximum obscuration for Ionization 4.00 % / ft		
	Maximum Obscuration for Photoelectric 6.00 % / ft		
	Resolution: 0.01% / ft		
	Average Battery Life: 8-10 hrs testing on a full charge		
	Calibration: Auto Self-Calibrates before each test		
	Operating Temp. 50 Degrees F. to 95 Degrees F		
	Humidity between 0-85%		
	Max Weight: 7 pounds incl. aerosol canister		
	Average Testing per aerosol Canister (100)		
	Aerosol: Environmentally Friendly, non-Flammable, non-Toxic, Safety Data Sheet Available		
	1 Year Minimum Warranty		

SPECIFICATIONS

FR0943986

Page 2 of1

2	Solo 461 Cordless Heat Detector Tester		
	For Heat Testing		
	Battery powered UL listed Charger included		
	Suits Fixed Temperature, Rate-of-rise and combination detectors		
	Detector manufacturer approved		
	Heat is directed horizontally at the sensor		
	Comes with two battery batons that fit inside Solo poles and a fast charger		
	Cross Air Technology (CAT)		
	Rechargeable at vehicle		
	No flame		
	1 year Min. Warranty		
3	SOLO A4 SMOKE DETECTOR TESTER		
	Oil free formulation		
	No lasting residue		
	Detector component compatibility		
	Non-Flammable		
	UL listed		
	Can size min. 10.0 oz		